PART NO: ABSHS-04

2010UP CHEVROLET CAMARO HOOD SCOOP

PLEASE READ THESE INSTRUCTIONS CAREFULLY PRIOR TO INSTALLATION

Important Note: Please inspect your hood scoop for proper fit before painting or mounting

Installation Instructions

Hardware Kit (Supplied on each hood scoop)

1. Locator = 1 pc 2. Washers = 2 pcs 3. Screws = 2 pcs

Tools Required:-

- Isopropyl alcohol or equivalent / Phillips Screwdriver / Masking Tape / Vacuum Cleaner / Centre Punch / Hand Drill / Drill Bits : 3/16" and 5/16" / Hammer

Hood Scoop Installation :-

Step 1

1. Clean surface area that is to be covered by the hood scoop with isopropyl alcohol or equivalent.

Step 2

2. Remove the trim underneath the hood. Note: Set the trim aside as it is to be re-attached to the vehicle after the installation of the hood scoop

Step 3

3. Peel the tape backing of the locator strip and attach it to the mounting holes of the hood scoop (illustration 1)

Step 4

4. Set the hood scoop on the center line of the hood and at a position where you get the best fit. **Step 5**

5. Tape the locator strips on the hood, carefully remove the hood scoop leaving the locator strips. (illustration 2)

Step 6

6. Center punch the holes for drilling. Drill 3/16" holes on the two punch mark locations. Enlarge the holes using 5/16" drill. Use minimum pressure when drilling to avoid denting of hood

Sten 7

7. Peel the tape backing at the corner (illustration 3) and tighten the two screws.

Step 8

8. Peel the tape backing completely and press the hood scoop gently onto the hood.

Step 9

9. Peel the tape backing of the grill and install it into grill cavity of the hood scoop. (illustration 4) **Step 10**

10. Hood scoop with grill installed. (illustration 5)

^{*}Refer to illustrations on next page

PART NO: ABSHS-04 2010UP CHEVROLET CAMARO HOOD SCOOP

PLEASE READ THESE INSTRUCTIONS CAREFULLY PRIOR TO INSTALLATION

Important Note: Please inspect your hood scoop for proper fit before painting or mounting

Illustrations

4)

1)





2)





3)

